

NOTE "D": ITEM 912 – COMPACTED GRANULAR BACKFILL: THIS METHOD OF BACKFILL CAN ONLY BE USED WITH FULL TIME COUNTY INSPECTION. AN INSPECTION FEE MUST BE POSTED BEFORE THE PERMIT WILL BE ISSUED. WHEN CITY OF COLUMBUS ITEM 912 IS SPECIFIED, ITEM 203.03 GUIDELINES SHALL BE USED.

NOTE "E": WHEN USING CDF, THE OPTIONAL FILL AREA OVER THE CONDUIT MAY BE BACKFILLED WITH SAND, GRANULAR MATERIAL, OR OTHER SUITABLE 912 MATERIAL, FOR A DISTANCE NOT TO EXCEED 1'-0". A PROTECTIVE BARRIER OF VISQUEEN OR SIMILAR MATERIAL IS PERMITTED.

NOTE "F": THE TRENCH WIDTH FOR SMALL PIPES AND CONDUITS SHALL BE OF SUFFICIENT WIDTH TO ALLOW FOR PROPER PLACEMENT OF THE BACKFILL MATERIAL. THE PAVEMENT PORTION OF THE TRENCH SHALL BE A MINIMUM OF 2'-0" IN WIDTH. THIS IS TO ALLOW FOR PROPER COMPACTION OF THE ASPHALT PAVEMENT. IF THE TRENCH FOR PLACING THE CONDUIT IS NARROWER THAN 2'-0" THEN THE PAVEMENT PORTION SHALL BE CUT BACK TO PROVIDE THE 2'-0" MINIMUM FOR PAVING OPERATIONS.

NOTE "G": WHEN PLATES ARE USED FOR THE STREET CROSSINGS, THEY SHALL BE SPIKED AND COLD PATCHED IN PLACE WITH ADVANCED WARNING SIGNS ERECTED. NO PLATES SHALL BE PERMITTED TO BE LEFT IN PLACE OVER NIGHT BETWEEN THE DATES OF NOV. 15TH & APR. 15TH (OR AS DIRECTED BY THE COUNTY ENGINEER) FOR SAFETY AND SNOW REMOVAL.

NOTE "H": USE OF ITEM 304 OR ITEM 912 FOR TYPE II PAVEMENT REPAIR SHALL BE APPROVED BY THE COUNTY ENGINEER BEFORE THE PERMIT WILL BE ISSUED.

CHRIS E. BAUSERMAN, P.E., P.S. Delaware County Engineer <hr/> <i>Delaware County Engineer</i>		STANDARD CONSTRUCTION DRAWING PAVEMENT & UTILITY CUT REPAIR STANDARDS	DELAWARE COUNTY ENGINEER'S OFFICE 50 Channing Street Delaware, Ohio 43015 PHONE: (740)833-2400 FAX: (740)833-2399 www.co.delaware.oh.us
APPROVED 1-22-2008	REVISED 1-04-2010	Drawn <u>KS</u> Checked <u>EM</u>	sheet <u>3</u> of <u>3</u> FILE NO. DCED-R1441C