

AGGREGATE BASE SHALL BE ELIMINATED WHEN CONTROLLED DENSITY FILL, ITEM 636, TYPE I OR II IS USED FOR COMPACTED BACKFILL.

ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE DELAWARE COUNTY DESIGN, CONSTRUCTION AND SURVEYING STANDARDS MANUAL, CURRENT EDITION.

BACKFILL OF ALL TRENCHES SHALL BE IN ACCORDANCE WITH STANDARD DRAWING R2160A AND R1441A.

TEMPORARY REPAVEMENT SHALL BE PLACED ON THE SAME DAY THE ORIGINAL PAVEMENT IS CUT. PERMANANT PAVEMENT SHALL BE PLACED WITHIN 48 HRS OF THE TEMPORARY PAVEMENT.

ALTERNATE BACKFILL - CONTROLLED DENSITY FILL ITEM 636, TYPE I OR II

CHRIS E. BAUSERMAN, P.E., P.S. Delaware County Engineer Delaware County Engineer	STANDARD CONSTRUCTION DRAWING PAVEMENT REPLACEMENT (TEMPORARY)	DELAWARE COUNTY ENGINEER'S OFFICE 50 Channing Street Delaware, Ohio 43015 PHONE: (740)833-2400 FAX: (740)833-2399 www.co.delaware.oh.us
APPROVED REVISED 1-04-2010		Drawn KS sheet 1 FILE NO. Checked EM of 1 DCED-R2161